


CD-UA Cross Connector Super Premium C5

Product description:

CD-UA cross connector with high resistance against corrosion for securing a strong cross-tie between the load carrying UA 50 and fastened CD 60 profile in constructing double level suspended ceilings.

Steel thickness: 0.9 mm



Standard Classification:

In compliance with **EN 13964:2014**
Category for Protection Against Corrosion, acc. EN ISO 12944-2:
Class C5 Highest Level of Protection



Aggressive Environment Examples - Class C5:

- External
 - Industrial zones, coastal areas and buildings near the beach with high levels of salt in the air.
- Internal
 - Buildings and areas subject to constant condensation, intense humidity and high levels of pollutants e.g. sea water or thermal baths.

Technical Data:

Parameters:	Value:
Steel thickness	0.9 mm
Reaction to fire	A1
Corrosion resistance class	Class B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.58 kN

Packaging and Storage:

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered, and ventilated area.

Safety recommendations:

- ✓ Product is not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. 2024©