

Special Adjusting Bracket

Description:

Special Adjusting Bracket for fixing a CD 60 profile directly to the main ceiling (concrete, wooden grid, etc.).

Modified design for more convenient handling and application.

The grey-coloured zinc coating guarantees the vast corrosion resistance of the element.

Available Sizes: 120 mm

Metal thickness: 0.8 mm



Standard Classification:

In compliance with **EN 13964:2014**




Advantages:

- ✓ Innovative, centrally positioned rib design, for increased stability and recommended load carrying capacity (min 0,40 kN)
- ✓ Uniform metal thickness of 0,8 mm, for added strength
- ✓ Easy levelling due to the shoulder positioned service holes
- ✓ Minimized loss of useful space in the room
- ✓ Quick and easy application

Technical Data:

Parameters:	
Steel thickness	0.8 mm
Reaction to fire	A1
Corrosion resistance class:	B
Recommended load-bearing capacity F	0.40 kN
Max. load-bearing capacity admF	0.90 kN



Packaging and Storage:

Product	Dimensions L _w / d _w	Thickness	Box
Special Adjusting Bracket 120	115 / 60 mm	0.8 mm	100 pcs

- ✓ 100 pieces in every box. Packaged in distinctive green Technogips Pro boxes.
- ✓ Store in a dry, covered and ventilated area.

Safety recommendations:

- ✓ Product is not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification. 2024©