

Exterior Pro Plus Screw 4.2 mm

Premium screws designed for Blue Board and Permabase

DESCRIPTION

Exterior Pro Plus Screw, specially designed screws, made of stainless steel, guaranteeing long life and flowless protection against corrosion.

Exterior Pro Plus Screw SN 4.2, self-tapping screw for fixing Blue Board and Permabase to timber structures and metal profiles with metal thickness up to 0.7 mm.

Exterior Pro Plus Screw SB 4.2, self-drilling screw for fixing Blue Board and Permabase to timber structures and metal profiles with metal thickness up to 2.0 mm.

Applicable both in exterior and interior drywall construction systems Technogips Pro.



Exterior Pro Plus Screw SN 4.2



Exterior Pro Plus Screw SB 4.2



QUALITY GUARANTEE



TECHNICAL DATA

Material	Stainless steel
Reaction to fire	A1
Drilling time requirement	< 2 sec.
Pull-out resistance	> 450 N
Thread	Double thread (Hi-Lo)
Bit type	PH2

ADVANTAGES

- ✓ Sharp tip for effortless drilling
- ✓ Without initial drilling
- ✓ Stainless steel
- ✓ Long service life
- ✓ Suitable for the industrial and coastal areas
- ✓ PH 2 bit in each box
- ✓ In compliance with EN 14566:2008

LENGTHS APPLICATION

PRODUCT	Connection (board, construction)
Exterior Pro Plus Screw 4,2 x 25 mm	12,5 mm - single-layer, metal construction
Exterior Pro Plus Screw 4,2 x 39 mm	12,5 mm - single-layer, timber construction
	12,5 mm - double layered, metal construction
Exterior Pro Plus Screw 4,2 x 55 mm	12,5 mm - double layered, timber construction
	12,5 mm - triple-layered, metal construction

Exterior Pro Plus Screw 4.2 mm

Premium screws designed for Blue Board and Permabase

DIMENSIONS AND PACKAGING

PRODUCT	DIAMETER (mm)	LENGTH (mm)	BIT	BOX (pcs)
Exterior Pro Plus Screw SN 4.2 x 25	4.2	25	PH 2	1000
Exterior Pro Plus Screw SN 4.2 x 39	4.2	39	PH 2	500
Exterior Pro Plus Screw SN 4.2 x 55	4.2	55	PH 2	250
Exterior Pro Plus Screw SB 4.2 x 25	4.2	25	PH 2	1000
Exterior Pro Plus Screw SB 4.2 x 39	4.2	39	PH 2	500
Exterior Pro Plus Screw SB 4.2 x 55	4.2	55	PH 2	250

- ✓ Packaged in distinctive green Technogips Pro boxes with included PH2 screw bit.
- ✓ Store in a dry, well-ventilated area.

APPLICATION

- ✓ Facades, sheathing of eaves, bay windows and soffits.
- ✓ Interior suspended ceilings, partitions or shaft walls in premises with high humidity, including condensation.
- ✓ Industrial and coastal areas, and others with high content of pollutants in the air that might cause corrosion and deterioration of the materials.

SAFETY RECOMMENDATIONS

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro manufactures and develops a wide range of construction products for various applications divided into the following product categories:

- ✓ Drywall System Solutions;
- ✓ Lightweight Facade Systems;
- ✓ Systems for fire protection and sound insulation;
- ✓ Gypsum-based plasters and finishes;

Technogips Pro also provides various technical information such as CAD details, detailed technical statements, specification clauses, application manuals and technical support both for contractors and consultants' offices as well as construction sites visits. For further information on our products and systems kindly check our website or contact your local Technogips Pro representative.

Formatt Building Products Ltd.

Office address

Sofia1404,
49B Bulgaria Blvd.,
www.technogipspro.com
sales@technogipspro.com

FORMATT

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification.

2024©