

Collated Exterior Pro Screw 4.2 mm

Specially designed for Blue Board and Permabase

DESCRIPTION

Collated Exterior Pro Screws, specially designed screws with zinc coating, guaranteeing supreme protection against corrosion.

Collated Exterior Pro Screw SN 4.2, self-tapping screw designed for fixing Blue Board and Permabase to timber structures and metal profiles with metal thickness up to 0.7 mm.

Collated Exterior Pro Screw SB 4.2, self-drilling screw designed for fixing Blue Board and Permabase to timber structures and metal profiles with metal thickness up to 2.0 mm.


Applicable both in exterior and interior drywall construction systems Technogips Pro.

QUALITY GUARANTEE



In compliance with **EN 14566:2008**

Class of Protection Against Corrosion,
acc. **EN ISO 12944-2**



Collated Exterior Pro Screw SN 4.2



Collated Exterior Pro Screw SB 4.2



TECHNICAL DATA

Material	Carbon Steel
Reaction to fire	A1
Protection against corrosion	720 hrs.
Drilling time	< 2 sec.
Pull-out resistance	> 450 N
Thread	Double thread (Hi-Lo)
Bit type	PH2

ADVANTAGES

- ✓ Needle point or self-drilling tip for effortless drilling
- ✓ Fastening collated screws saves time and significantly increases work efficiency and productivity
- ✓ Unified belts are suitable for all types of collated screwdrivers
- ✓ Without initial drilling
- ✓ Supreme anti-corrosion coating
- ✓ PH 2 bit in each box
- ✓ Suitable for industrial and coastal areas
- ✓ Highest class of protection against corrosion according to EN ISO 12944-2

LENGTHS APPLICATION

PRODUCT	Connection (board, construction)
Collated Exterior Pro Screw 4,2 x 25 mm	12,5 mm - single-layer, metal construction
Collated Exterior Pro Screw 4,2 x 39 mm	12,5 mm - single-layer, timber construction
	12,5 mm - double layered, metal construction

Collated Exterior Pro Screw 4.2 mm

Specially designed for Blue Board and PermaBase

DIMENSIONS AND PACKAGING

PRODUCT	DIAMETER (mm)	LENGTH (mm)	BIT	BOX (pcs)	BOX (pcs) / CARTON
Collated Exterior Pro Screw SN 4.2 x 25	4.2	25	PH 2	1000	10
Collated Exterior Pro Screw SN 4.2 x 39	4.2	39	PH 2	1000	10
Collated Exterior Pro Screw SB 4.2 x 25	4.2	25	PH 2	1000	10
Collated Exterior Pro Screw SB 4.2 x 39	4.2	39	PH 2	1000	10

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, well-ventilated area

APPLICATION

- ✓ Facades, sheathing of eaves, bay windows and soffits.
- ✓ Interior suspended ceilings, partitions or shaft walls in premises with high humidity, including condensation.
- ✓ Industrial and coastal areas, and others with high content of pollutants in the air that might cause corrosion and deterioration of the materials.



SAFETY RECOMMENDATIONS

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.

Technogips Pro manufactures and develops a wide range of construction products for various applications divided into the following product categories:

- ✓ Drywall System Solutions;
- ✓ Lightweight Facade Systems;
- ✓ Systems for fire protection and sound insulation;
- ✓ Gypsum-based plasters and finishes;

Technogips Pro also provides various technical information such as CAD details, detailed technical statements, specification clauses, application manuals and technical support both for contractors and consultants' offices as well as construction sites visits. For further information on our products and systems kindly check our website or contact your local Technogips Pro representative.

Formatt Building Products Ltd.

Office address

Sofia1404,
49B Bulgaria Blvd.,
www.technogipspro.com
sales@technogipspro.com

FORMATT

Technogips Pro reserves the right to change any of the specifications and technical data mentioned in the Technical Data Sheets at its sole discretion without prior notification.

2026©