

Self-drilling Screw TEX with flat head

Product description:

Special Self-drilling Screw TEX with flat head is designed for connecting metal profiles or for fixing Adjusting Brackets to CD 60 profiles. Fasten elements with a collective thickness up to 2 mm.

The grey coloured Zink coating guarantees the vast corrosion resistance of the element.

Available Sizes: 4.2 x 13 mm



Standard Classification:

In compliance with **EN 14566:2008**
Type **LB**



Advantages:



- ✓ PH 2 screw plug



- ✓ Flat screw head to provide additional protection against cracks when installing gypsum plasterboards.



- ✓ Self-drilling point and specially designed thread help to drill the metal profile directly, with ease.

Technical Data:

Parameters:	Specification:
Reaction to fire	A1
Corrosion resistance classification	48 hrs
Drilling time requirement	< 2 sec

Storage:

Product	d _w x L _w	Box	Boxes in a carton
Self-drilling Screw TEX 4.2 x 13	4.2 x 13 mm	1000 pcs	32 units

- ✓ Packaged in distinctive green Technogips Pro boxes
- ✓ Store in a dry, covered and ventilated area

Safety recommendations:

- ✓ Product not classified as hazardous.
- ✓ The use of safety gloves is strongly advisable when working with this product, in prevention from physical harm.